

ALL PRODUCTS FEATURE:

- FULL DEPLOYMENT IN UNDER 15 SECONDS
- FIVE YEAR WARRANTY
- ALL WEATHER (NOT AFFECTED BY ICE BUILD UP, HIGH WINDS, BLOWING DUST)

- ABILITY TO OVERHANG SIDE OF VEHICLE
- ALL ELECTRIC (No air or hydraulics required)
- MAINTENANCE FREE
- NFPA 1901 COMPLIANT
- TESTED TO 90 MPH WIND

MODEL No.	DESCRIPTION*	POWER REQUIRED
KL411	6 X 100 Watts Quartz	48 Amps, 12 VDC
KL415-MH	4 X 150 Watts Metal Halide**	48 Amps, 12 VDC
KL435	6 X 350 Watts Quartz	2 KW, 110 or 220 VAC
KL450	6 X 500 Watts Quartz	3 KW, 110 or 220 VAC
KL465	6 X 650 Watts Quartz	4 KW, 110 or 220 VAC
KL475***	6 X 750 Watts Quartz	5 KW, 110 or 220 VAC

*Lumens per light head 110W = 2500 / 150W Metal Halide = 11,250
 350W HIR = 10,000 / 500W = 11,100 / 650W HIR = 25,200
 (Note: 650W HIR not for use on PTO Generators) / 75W = 16,500

**Instant Hot Restrike Wt. 165lbs., 75kg., Height 13" (330)

***750 Watt • Bulbs available only with FRC or Havis Shields lamp Heads

OPTIONS

- BACK LIGHTING
- TOP MOUNTED STROBE
- PANEL MOUNTED CONTROLS
- OTHER LIGHTING PACKAGES AVAILABLE INCLUDING METAL HALIDE



Havis Shields



FRC Optima



Strobe



Optional backlighting use bottom two lights for down lighting or backlight additional area.

ALL KNIGHT² FEATURES

- FULL DEPLOYMENT IN UNDER 15 SECONDS
- ALL WEATHER (not affected by ice buildup, high winds, blowing dust)
- ABILITY TO OVERHANG SIDE OF VEHICLE
- ONE TOUCH AUTO PARK
- UMBILICAL REMOTE CONTROLLER WITH 15 FT. CORD
- ALL ELECTRIC (No air or hydraulics required)
- CONTINUOUS 360° ROTATION
- MAINTENANCE FREE
- FIVE YEAR WARRANTY
- NFPA 1901 COMPLIANT
- TESTED TO 90 MPH WIND

